NSN 6625-01-166-8079

Voltmeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-166-8079

| Dc |
|---|
| Overall Length: |
| 2.480 inches |
| Overall Height: |
| 2.702 inches |
| Overall Width: |
| 2.702 inches |
| Scale Division Quantity: |
| 30 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.252 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.180 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Pointer Color: |
| Black single indicator single range |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+300.0 volts, dc single indicator single range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |

NSN 6625-01-166-8079

Voltmeter - Page 2 of 2



| Movement Suspension Method: |
|---|
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A310a0