

View Online at <https://aerobasegroup.com/nsn/6625-01-171-1800>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.062 inches

Mounting Hole Diameter:

0.203 inches

Scale Division Quantity:

60 single indicator 4th range

Overall Diameter:

4.500 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.062 inches

Furnished Items And Quantity:

Nut 7; lockwasher 5; seal 1; shunt wire 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

60.0 volt-amperes

Dial Scale Marking Color:

Black single indicator all ranges and green single indicator all ranges and red single indicator all ranges

Accuracy In Percent:

-1.25/+1.25 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.531 inches

Meter Body Diameter Behind Mounting Flange:

3.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

+0.0/+60.0 volts, dc single indicator 4th range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0