NSN 6625-01-171-3566

Voltmeter - Page 1 of 2

1 clamp and 2 threaded stud

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-171-3566

Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.410 inches
Scale Division Quantity:
11 single indicator single range
Mounting Stud Length:
0.570 inches
Overall Diameter:
2.300 inches
Environmental Protection:
Dust resistant
Distance Between Mounting Facility Centers:
1.320 inches
Furnished Items And Quantity:
Clamp 1; nut 5; washer 10
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Two hole/stud
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.140 inches
Meter Body Diameter Behind Mounting Flange:
2.060 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range and orange single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:

NSN 6625-01-171-3566

Voltmeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+16.0/+36.0 volts, $$ dc single indicator single range
Mounting Stud Diameter:
0.138 inches
Scale Selection Method:
Terminal
Features Provided:
Self-illumination facility
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
3 threaded stud
Operating Voltage Rating In Volts:
26.0 dc
Special Features:
Sealed bezel
Special Markings:
Special Markings: Nec. Grd. Stamped on side of case
-
Nec. Grd. Stamped on side of case
Nec. Grd. Stamped on side of case Material:
Nec. Grd. Stamped on side of case Material: Steel
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature:
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment:
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator:
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator: Round flush mtg
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator: Round flush mtg Shelf Life:
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator: Round flush mtg Shelf Life: N/a
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator: Round flush mtg Shelf Life: N/a
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
Nec. Grd. Stamped on side of case Material: Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Zinc Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: