

View Online at <https://aerobasegroup.com/nsn/6625-01-171-3566>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.410 inches

Scale Division Quantity:

11 single indicator single range

Mounting Stud Length:

0.570 inches

Overall Diameter:

2.300 inches

Environmental Protection:

Dust resistant

Distance Between Mounting Facility Centers:

1.320 inches

Furnished Items And Quantity:

Clamp 1; nut 5; washer 10

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.140 inches

Meter Body Diameter Behind Mounting Flange:

2.060 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range and orange single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+16.0/+36.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 threaded stud

Operating Voltage Rating In Volts:

26.0 dc

Special Features:

Sealed bezel

Special Markings:

Nec. Grd. Stamped on side of case

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Zinc

Style Designator:

Round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0