

View Online at <https://aerobasegroup.com/nsn/6625-01-173-9957>

Circuit Current For Which Designed:

Ac

Overall Length:

2.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.990 inches and 4.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.552 inches and 3.572 inches

Overall Height:

4.410 inches

Overall Width:

4.850 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+55.000/+65.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.210 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

240.0 ac

Phase:

Single

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0