

View Online at <https://aerobasegroup.com/nsn/6625-01-174-8641>

Circuit Current For Which Designed:

Dc

Overall Length:

3.335 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches

Overall Height:

2.120 inches

Overall Width:

3.745 inches

Mounting Stud Length:

0.510 inches

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Meter Depth Behind Mounting Flange:

2.960 inches

Meter Body Width Behind Mounting Flange:

3.000 inches

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Display Type:

Light emitting diode

Display Digit Quantity:

4-1/2

Measurement Range:

-1.9999/+1.9999 volts, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.760 inches

Features Provided:

External shunting and self-illumination facility

Accuracy Rating:

Porm 0.02 pct of reading porm 2 count single indicator single range

Display Color:

Red, light single indicator single range

Circuit Attachment Method And Quantity:

1 connector, plug

Special Features:

Automatic zero adjustment

Nuclear Hardness Critical Feature:

Nonhardened

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0