

View Online at <https://aerobasegroup.com/nsn/6625-01-175-1699>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

68.5 millimeters

Scale Division Quantity:

2 single indicator single range

Mounting Stud Length:

33.5 millimeters

Overall Diameter:

59.0 millimeters

Environmental Protection:

Windproof

Distance Between Mounting Facility Centers:

22.0 millimeters

Furnished Items And Quantity:

Bracket assembly 1; gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Green single indicator single range and red single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

61.5 millimeters

Meter Body Diameter Behind Mounting Flange:

52.0 millimeters

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

Red zone left side of scale, green zone right side of scale

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

5.0 millimeters

Features Provided:

Rfi shielding

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Earthquake proof

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Zinc

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0