

View Online at <https://aerobasegroup.com/nsn/6625-01-175-4843>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 4.4312 inches and 6.9302 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.421875 inches

Overall Width:

4.421875 inches

Scale Division Quantity:

51 single indicator all ranges

Mounting Stud Length:

0.625 inches

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

Between 3.7505 inches and 6.2495 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+300.0 volts, dc single indicator 2nd range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0