

View Online at <https://aerobasegroup.com/nsn/6625-01-175-4848>

Circuit Current For Which Designed:

Ac

Overall Length:

2.880 inches

Mounting Hole Diameter:

0.155 inches

Scale Division Quantity:

40 single indicator single range

Frequency Rating:

400.0 hertz

Overall Diameter:

4.500 inches

Mounting Bolt Circle Diameter:

4.250 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.6 volt-amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.3/+0.3 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.530 inches

Meter Body Diameter Behind Mounting Flange:

3.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+380.0/+420.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 110.0 ac and 120.0 ac

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0