NSN 6625-01-177-2794

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-177-2794

| Circuit Current For Which Designed: |
|---|
| Ac |
| Overall Length: |
| 10.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.688 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.688 inches |
| Overall Height: |
| 4.500 inches |
| Overall Width: |
| 4.500 inches |
| Mounting Hole Diameter: |
| 0.312 inches |
| Scale Division Quantity: |
| 5 single indicator single range |
| Frequency Rating: |
| 400.0 hertz |
| Overall Diameter: |
| 3.960 inches |
| Furnished Items And Quantity: |
| Scrws 4, hex head nuts 4, lock washers 4 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -0.023/+0.023 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 9.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.960 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |

Pointer Color:

Black single indicator single range

NSN 6625-01-177-2794

Voltmeter - Page 2 of 2



| Power Source: |
|---|
| External |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +110.0/+120.0 volts, af single indicator single range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| High impact, shock resisent |
| Material: |
| Plastic or steel |
| Style Designator: |
| Round flush mtg w/4 tabs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |