

View Online at <https://aerobasegroup.com/nsn/6625-01-178-4020>

**Scale Marking And Surface Finish:**

Letters nonluminous

**Width:**

4.422 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.376 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.376 inches

**Length:**

6.957 inches

**Scale Division Quantity:**

2 single indicator single scale

**Current Type:**

Ac

**Ac Voltage Rating:**

120.0 volts

**Frequency Rating:**

400.0 hertz

**Mounting Stud Length:**

0.625 inches

**Presentation Type:**

Dial

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Individual Marking:**

Two arrows: top left and right; slow under left arrow; fast under right arrow

**Electrical Connection Quantity:**

4

**Pointer Purpose:**

Difference between two signals

**Pointer Type:**

Indicating single pointer

**Mounting Facility Type And Quantity:**

4 threaded stud

**Mounting Stud Diameter:**

0.250 inches

**Accuracy Rating:**

2.0 arc angle in degrees single indicator single scale

**Features Provided:**

Mounting hardware and waterproof

**Case Material:**

Plastic

**Phase:**

Single

**Height:**

4.422 inches

**Test Data Document:**

81349-mil-s-16104 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-16104 rev b government specification

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A53400