

View Online at <https://aerobasegroup.com/nsn/6625-01-178-4020>

Scale Marking And Surface Finish:

Letters nonluminous

Width:

4.422 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Length:

6.957 inches

Scale Division Quantity:

2 single indicator single scale

Current Type:

Ac

Ac Voltage Rating:

120.0 volts

Frequency Rating:

400.0 hertz

Mounting Stud Length:

0.625 inches

Presentation Type:

Dial

Mounting Arrangement Style:

Four hole/stud rectangular/square

Individual Marking:

Two arrows: top left and right; slow under left arrow; fast under right arrow

Electrical Connection Quantity:

4

Pointer Purpose:

Difference between two signals

Pointer Type:

Indicating single pointer

Mounting Facility Type And Quantity:

4 threaded stud

Mounting Stud Diameter:

0.250 inches

Accuracy Rating:

2.0 arc angle in degrees single indicator single scale

Features Provided:

Mounting hardware and waterproof

Case Material:

Plastic

Phase:

Single

Height:

4.422 inches

Test Data Document:

81349-mil-s-16104 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-16104 rev b government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A53400