NSN 6625-01-178-4120

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-178-4120

Circuit Current For Which Designed:
Dc .
Overall Length:
1.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches
Overall Height:
1.810 inches
Overall Width:
1.810 inches
Mounting Hole Diameter:
0.125 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Furnished Items And Quantity:
Nut 4; washer 4; screw 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range

Scale Marking:

Go-no go scale 0 to 200 microamps dc

NSN 6625-01-178-4120

Special Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304/24c
Style Designator:
Rectangular flush mtg
Supplementary Features:
Internal res 15 kohm porm 1 pct
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0