

View Online at <https://aerobasegroup.com/nsn/6625-01-178-6809>

Circuit Current For Which Designed:

Dc

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.318 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.318 inches

Overall Height:

1.810 inches

Overall Width:

1.810 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Mtg hardware

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+200.0 amperes, dc single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0