

View Online at <https://aerobasegroup.com/nsn/6625-01-178-7633>

**Overall Depth:**

21.000 inches

**Overall Height:**

3.500 inches

**Overall Width:**

19.000 inches

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

Between 47.0 hertz and 63.0 hertz

**End Application:**

Required for wwmccs intercomputer newtwork testing

**Electrical Power Source Relationship:**

Alternate operating

**Unpackaged Unit Weight:**

23.750 pounds

**Phase:**

Single

**Special Features:**

Mounting standard rack; non-tilting slides provided; the -19 in the part number indicates the this item has 19 frequencies (this info listed in fflid); measurement and display on three 6 digit indicators: bit errors, block errors, total blocks or bit errors, second errors, elapsed seconds; front panel selection of 19 clock rates

**Functional Description:**

P/n 604-19 provides digital test capabilities of data rates 1.2, 2.4, 4.8, 9.6, 16, 19.2, 50, 56, 128, 256, 512, 772, 1544, 2048, 3152, 6312, 8448, 12928, 2000 kb/s; interface rs232c; impedance: 78 ohms balanced, 100 ohms unbalanced and 135 ohms balanced

**Supplementary Features:**

Manufacturers name: data transmission test set; bit error test set

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T263-c