

View Online at <https://aerobasegroup.com/nsn/6625-01-191-5855>

Current Type:

Ac and dc

Direct Current Rating In Amps:

3.5

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Accessory Components And Quantity:

Test adaptor 1; 9-pin cable-mountplug 1; 18-in. Test leads 2; instruction manual 1

Voltage Rating:

Between 90.0 volts and 250.0 volts

Screen Size:

8 by 10 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Trigger Sweep Polarity Switch:

Not included

Input Intensity Modulation Feature:

Not provided

Frequency Response Rating:

Not provided

X-axis Frequency Response Rating:

1.0 megahertz

Y-axis Frequency Response Rating:

1.0 megahertz

Measurement Range Quantity:

6

Calibrated Screen Scale:

Included

Camera Recording Device Accommodation:

Provided

Special Features:

500 mhz at 10 mv/div; 700 ps risetime; 500 ps/div fastest calibrated sweep rate; plus 2.5 cm/ns writing speed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g