

View Online at <https://aerobasegroup.com/nsn/6625-01-193-8481>

Circuit Current For Which Designed:

Ac

Overall Length:

2.110 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.736 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.370 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.530 inches

Environmental Protection:

Water resistant

Shortest Horizontal Distance Between Mounting Centers:

1.368 inches

Furnished Items And Quantity:

Gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.610 inches

Meter Body Diameter Behind Mounting Flange:

2.720 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Mounting Stud Diameter:

0.112 inches

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 110.0 ac and 130.0 ac

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0