

View Online at <https://aerobasegroup.com/nsn/6625-01-195-1420>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.110 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.736 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.370 inches

**Overall Height:**

3.500 inches

**Overall Width:**

3.500 inches

**Scale Division Quantity:**

30 single indicator single range

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Mounting Stud Length:**

0.530 inches

**Environmental Protection:**

Water resistant

**Shortest Horizontal Distance Between Mounting Centers:**

1.368 inches

**Furnished Items And Quantity:**

Gasket 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud triangular

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.610 inches

**Meter Body Diameter Behind Mounting Flange:**

2.720 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+150.0 amperes, ac single indicator single range

**Mounting Stud Diameter:**

0.112 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0