

View Online at <https://aerobasegroup.com/nsn/6625-01-196-3512>

Circuit Current For Which Designed:

Ac

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Overall Height:

4.250 inches

Overall Width:

4.250 inches

Mounting Stud Length:

0.500 inches

End Application:

Alsf-2, fa-9993/c constant current regulator

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Diameter Behind Mounting Flange:

2.500 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+25.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Functional Description:

Ammeter, scale 0 to 20 amps

Material:

Steel

Reference Data And Literature:

3m1, ti-6850.56, instruction book, dual mode high intensity approach lighting system alsf-2/ssalr, pg 8-20

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Elec, elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0