

View Online at <https://aerobasegroup.com/nsn/6625-01-200-1323>

Circuit Current For Which Designed:

Dc

Overall Length:

2.945 inches

Overall Height:

0.910 inches

Overall Width:

2.145 inches

Mounting Hole Diameter:

0.120 inches

Scale Division Quantity:

4 single indicator single range

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

Between 1.899 inches and 1.913 inches

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

10.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.988 inches

Meter Body Width Behind Mounting Flange:

1.710 inches

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

E; 1/2; f

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

0.680 inches

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Day glow red pointer

Special Markings:

5 scale lines

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular semi-flush mtg

Specification Data:

55296-st-20684-1 manufacturers source control

Fsc Application Data:

Test set, elect, equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0