

View Online at <https://aerobasegroup.com/nsn/6625-01-200-1324>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.760 inches

Overall Height:

0.500 inches

Overall Width:

1.810 inches

Environmental Protection:

Cold resistant and fungus resistant and heat resistant and humidity resistant and salt water resistant and shock proof and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range and green single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.140 inches

Meter Body Width Behind Mounting Flange:

1.690 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range and yellow single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 bracket and 2 screw

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+70.0/+160.0 volts, ac single indicator single range

Meter Body Height Behind Mounting Flange:

0.500 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0