

View Online at <https://aerobasegroup.com/nsn/6625-01-200-1542>

Circuit Current For Which Designed:

Dc

Overall Length:

3.170 inches

Overall Height:

1.510 inches

Overall Width:

2.900 inches

Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

2.000 inches

End Application:

Radar set an/spg-55

Furnished Items And Quantity:

Washer 4

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Meter Depth Behind Mounting Flange:

2.610 inches

Meter Body Width Behind Mounting Flange:

2.760 inches

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket and 2 screw and 2 unthreaded hole

Display Type:

Light emitting diode

Display Digit Quantity:

4-1/2

Measurement Range:

-19.999/+19.999 volts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

1.290 inches

Accuracy Rating:

Porm 0.05 pct of reading porm 0.01 pct full scale single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

1 printed circuit

Operating Voltage Rating In Volts:

Between 4.8 dc and 6.0 dc

Special Features:

Ruggedized; ungrounded case

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Automatic zero cal

Specification Data:

53711-5618416 manufacturers specification control

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0