

View Online at <https://aerobasegroup.com/nsn/6625-01-200-4124>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

7.218 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.376 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.376 inches

**Overall Height:**

4.422 inches

**Overall Width:**

4.422 inches

**Mounting Hole Diameter:**

0.312 inches

**Scale Division Quantity:**

30 single indicator single range

**Frequency Rating:**

Between 25.0 hertz and 100.0 hertz

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.750 inches

**Meter Body Diameter Behind Mounting Flange:**

3.960 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+600.0 volts, ac single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic polycarbonate

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0