

View Online at <https://aerobasegroup.com/nsn/6625-01-201-8075>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.355 inches

**Overall Height:**

1.640 inches

**Overall Width:**

1.980 inches

**Mounting Stud Length:**

0.500 inches

**Distance Between Mounting Facility Centers:**

1.250 inches

**Furnished Items And Quantity:**

Nut 2; washer 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.820 inches

**Meter Body Diameter Behind Mounting Flange:**

1.355 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

-15.0/+3.0 decibels above or below one milliwatt single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Knife edge pointer

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 connector, receptacle

**Special Markings:**

15, -10, -5, 0, 1, 2, 3; dbm 50 ohms

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Electrical, electronic properties measuring and test instruments

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0