

View Online at <https://aerobasegroup.com/nsn/6625-01-201-8075>

Circuit Current For Which Designed:

Dc

Overall Length:

1.355 inches

Overall Height:

1.640 inches

Overall Width:

1.980 inches

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

1.250 inches

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.820 inches

Meter Body Diameter Behind Mounting Flange:

1.355 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-15.0/+3.0 decibels above or below one milliwatt single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Knife edge pointer

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 connector, receptacle

Special Markings:

15, -10, -5, 0, 1, 2, 3; dbm 50 ohms

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0