

View Online at <https://aerobasegroup.com/nsn/6625-01-202-2621>

Circuit Current For Which Designed:

Dc

Overall Length:

7.730 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 6.045 inches and 6.055 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.720 inches and 0.730 inches

Overall Height:

1.540 inches

Overall Width:

6.720 inches

Scale Division Quantity:

30 single indicator single range

Mounting Stud Length:

1.560 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Lock washers 4; hex nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

5.840 inches

Meter Body Width Behind Mounting Flange:

5.435 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

0, 5, 10, 15, 20, 25, 30; ihg

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.190 inches

Meter Body Height Behind Mounting Flange:

1.225 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0