

View Online at <https://aerobasegroup.com/nsn/6625-01-204-3293>

Circuit Current For Which Designed:

Dc

Overall Length:

3.650 inches

Overall Height:

Between 1.159 inches and 1.171 inches

Overall Width:

Between 4.369 inches and 4.381 inches

Mounting Hole Diameter:

Between 0.126 inches and 0.131 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

4.062 inches

Furnished Items And Quantity:

Nut 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range and green single indicator single range and red single indicator single range and yellow single indicator single range

Accuracy In Percent:

-0.5/+0.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.150 inches

Meter Body Width Behind Mounting Flange:

3.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-10.0/+10.0 volts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

0.560 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

6 threaded stud

Special Features:

Ruggedized

Special Markings:

Left; right

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0