NSN 6625-01-205-1971

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-205-1971

Circuit Current For Which Designed:
Dc
Overall Length:
2.850 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
3.510 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Screws 3; hex nuts 3; lock washers 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Buff single indicator single range
Pointer Color:
Rlack single indicator single range

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Power Source:

Scale Graduation Type:

Linear single indicator single range

NSN 6625-01-205-1971

Voltmeter - Page 2 of 2



Measurement Range:
+0.0/+50.0 volts, dc single indicator single range
Scale Selection Method:
Terminal
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Material:
Plastic and steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Round flush mtg
Test Data Document:
31349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-m-10304/11 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A310a0