NSN 6625-01-206-1234

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-206-1234

Dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

7.170 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 6.045 inches and 6.055 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.720 inches and 0.730 inches

Overall Height:

1.890 inches

Overall Width:

7.050 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Corrosion resistant and waterproof

Furnished Items And Quantity:

Lock washers 4; hex nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 5.750 inches and 5.840 inches

Meter Body Width Behind Mounting Flange:

5.430 inches

Movement Type:

Moving coil, permanent magnet

NSN 6625-01-206-1234

Special Scale Meter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Scale Marking:
0, 20, 40, 60, 80, 100; pct
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Mounting Stud Diameter:
0.190 inches
Meter Body Height Behind Mounting Flange:
1.190 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic and steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0