

View Online at <https://aerobasegroup.com/nsn/6625-01-206-1234>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

7.170 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 6.045 inches and 6.055 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.720 inches and 0.730 inches

Overall Height:

1.890 inches

Overall Width:

7.050 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Corrosion resistant and waterproof

Furnished Items And Quantity:

Lock washers 4; hex nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 5.750 inches and 5.840 inches

Meter Body Width Behind Mounting Flange:

5.430 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0, 20, 40, 60, 80, 100; pct

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.190 inches

Meter Body Height Behind Mounting Flange:

1.190 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0