

View Online at <https://aerobasegroup.com/nsn/6625-01-206-9358>

Circuit Current For Which Designed:

Ac

Overall Length:

7.090 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches

Overall Height:

2.810 inches

Overall Width:

3.900 inches

Mounting Hole Diameter:

0.138 inches

Frequency Rating:

Between 54.0 hertz and 440.0 hertz

Furnished Items And Quantity:

Screws 4; lock washers 4; hex nuts 4

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Meter Depth Behind Mounting Flange:

6.840 inches

Meter Body Width Behind Mounting Flange:

3.531 inches

Scale Marking:

0-359.9 degrees

Mounting Facility Type And Quantity:

4 unthreaded hole

Display Type:

Light emitting diode

Display Digit Quantity:

4

Meter Body Height Behind Mounting Flange:

1.720 inches

Accuracy Rating:

Porm 2 degrees of reading single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

1 connector, plug

Operating Voltage Rating In Volts:

115.0 ac

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0