

View Online at <https://aerobasegroup.com/nsn/6625-01-210-6585>

Circuit Current For Which Designed:

Ac or dc

Overall Length:

1.650 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.307 inches and 1.317 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.307 inches and 1.317 inches

Overall Height:

1.810 inches

Overall Width:

1.810 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

4 single indicator single range

Environmental Protection:

Airtight and cold resistant and dust resistant and explosion proof and fungus resistant and heat resistant and humidity resistant and sand proof and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 6; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 12.0 amperes single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Special Markings:

Indicator marked starter amps x 100

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0