

View Online at <https://aerobasegroup.com/nsn/6625-01-210-9163>

Circuit Current For Which Designed:

Ac

Overall Length:

6.460 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

5 single indicator single range

Frequency Rating:

400.0 hertz

Overall Diameter:

3.810 inches

Mounting Bolt Circle Diameter:

3.510 inches

Furnished Items And Quantity:

Screws 3; hex nuts 3; lock washers 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.23/+0.23 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

6.000 inches

Meter Body Diameter Behind Mounting Flange:

2.860 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+110.0/+120.0 volts, af single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic or steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-v-23151 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-v-23151 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0