

View Online at <https://aerobasegroup.com/nsn/6625-01-210-9741>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.030 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

50 single indicator 1st range

Overall Diameter:

2.695 inches

Environmental Protection:

Cold resistant and humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 7; lock washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.170 inches

Meter Body Diameter Behind Mounting Flange:

2.150 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

-10.0 to 0.0 decibels above or below one milliwatt single indicator 1st range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Material:

Steel

Surface Treatment:

Paint

Special Test Features:

Conforms to mil-m-10304, type mr26w050dcuar

Style Designator:

C1 round flush mtg

Supplementary Features:

Hardware screws are black finished

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0