

View Online at <https://aerobasegroup.com/nsn/6625-01-210-9974>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

20 single indicator single range

**Furnished Items And Quantity:**

Screws 4; lock washers 4; hex nuts 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

20.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Psig; 0; 50; 100; 150; 200

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Mr13w020spabr

**Material:**

Plastic and steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0