NSN 6625-01-211-1624

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-211-1624

| Circuit Current For Which Designed: |
|---|
| Dc |
| Overall Length: |
| 1.625 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Scale Division Quantity: |
| 35 single indicator single range |
| Overall Diameter: |
| 1.810 inches |
| Mounting Bolt Circle Diameter: |
| 1.610 inches |
| Furnished Items And Quantity: |
| Screws 3; lock washers 3; hex nuts 3 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.250 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.510 inches |
| Movement Type: |
| Moving coil, permanent magnet |

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 35.0 volts, dc single indicator single range

NSN 6625-01-211-1624 Voltmeter - Page 2 of 2



| Features Provided: | |
|---|--|
| Zero adjuster | |
| Movement Suspension Method: | |
| Jewel pivot base | |
| Circuit Attachment Method And Quantity: | |
| 2 threaded stud | |
| Material: | |
| Steel | |
| Nuclear Hardness Critical Feature: | |
| Nonhardened | |
| Style Designator: | |
| Round flush mtg | |
| Fsc Application Data: | |
| Test set, elect. Equip. | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A310a0 | |