

View Online at <https://aerobasegroup.com/nsn/6625-01-212-1586>

Circuit Current For Which Designed:

Ac

Overall Length:

1.820 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.180 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.060 inches

Overall Height:

4.060 inches

Overall Width:

5.180 inches

Scale Division Quantity:

100 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.138 inches

Furnished Items And Quantity:

Lock washers 4; hex nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.660 inches

Meter Body Diameter Behind Mounting Flange:

1.450 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-100.0 to 100.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.520 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic and steel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0