

View Online at <https://aerobasegroup.com/nsn/6625-01-212-7355>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

7.730 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 6.045 inches and 6.055 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 0.720 inches and 0.730 inches

**Overall Height:**

1.540 inches

**Overall Width:**

6.720 inches

**Scale Division Quantity:**

45 single indicator single range

**Mounting Stud Length:**

1.270 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Lock washers 4; hex nuts 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

5.840 inches

**Meter Body Width Behind Mounting Flange:**

5.435 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Red single indicator single range

**Scale Marking:**

0; 500; 1000; 1500; 2000; 2500; 3000; 3500; 4000; 4500; psig

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Mounting Stud Diameter:**

0.190 inches

**Meter Body Height Behind Mounting Flange:**

1.225 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Special Features:**

Two 6 volt incandescent lamps

**Material:**

Plastic

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0