NSN 6625-01-212-7356

Special Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

Between 6.045 inches and 6.055 inches

Between 0.720 inches and 0.730 inches

Overall Length: 7.730 inches

Overall Height: 1.540 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/6625-01-212-7356

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.720 inches
Scale Division Quantity:
30 single indicator single range
Mounting Stud Length:
1.270 inches
Environmental Protection:
Shock resistant and vibration resistant
Furnished Items And Quantity:
Lock washers 4; hex nuts 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.840 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Red single indicator single range
Scale Marking:
0; 50; 100; 150; 200; 250; 300; return

NSN 6625-01-212-7356

Special Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Mounting Stud Diameter:
0.190 inches
Meter Body Height Behind Mounting Flange:
1.225 inches
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
4 threaded stud
Special Features:
Two 6 volt incandescent lamps
Material:
Plastic
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0