

View Online at <https://aerobasegroup.com/nsn/6625-01-212-9864>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

5.710 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 3.360 inches and 3.390 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 3.360 inches and 3.390 inches

**Overall Height:**

4.330 inches

**Overall Width:**

4.330 inches

**Mounting Hole Diameter:**

0.313 inches

**Scale Division Quantity:**

75 single indicator single range

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Environmental Protection:**

Dust resistant and humidity resistant

**Furnished Items And Quantity:**

Lock washers 4; hex nuts 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.790 inches

**Meter Body Diameter Behind Mounting Flange:**

3.970 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 150.0 volts, ac single indicator single range

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic and steel

**Surface Treatment:**

Paint

**Special Test Features:**

Conforms to specification ansi c-39.1

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0