

View Online at <https://aerobasegroup.com/nsn/6625-01-215-6376>

Circuit Current For Which Designed:

Ac and dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Depth:

1.562 inches

Overall Length:

6.875 inches

Overall Width:

3.500 inches

Indicator Type:

Digital display

Installation Design:

Bench

Frequency Response Range:

+0.040 to 1.000 kilohertz

Background Color:

Gray, light single indicator all ranges

Power Source:

Internal

Display Type:

Liquid crystal

Display Digit Quantity:

3-1/2

Measurement Range:

+0.0 to 1500.0 volts, dc single indicator 14th range

Scale Selection Method:

Switch

Features Provided:

Electrical overload protection and internal battery accommodation and portable and overranging and warning feature

Accuracy Rating:

Porm 1.5 pct of reading porm 3 digits single indicator 6th range

Display Color:

Black single indicator all ranges

Circuit Attachment Method And Quantity:

2 phone jack and 2 probe, direct contact and 2 wire lead

Operating Voltage Rating In Volts:

9.0 dc

Phase:

Single

Special Features:

Buzzer on 0 to 200 ohms range

Style Designator:

Portable

Supplementary Features:

175 hr batt life

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0