

View Online at <https://aerobasegroup.com/nsn/6625-01-217-1746>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

2.059 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.766 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.766 inches

**Overall Height:**

2.250 inches

**Overall Width:**

2.250 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

30 single indicator single range

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Furnished Items And Quantity:**

Screws 4; lock washers 4; hex nuts 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.5 to 2.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.840 inches

**Meter Body Diameter Behind Mounting Flange:**

2.062 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 30.0 amperes, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Red accent mark at 20 amps

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0