

View Online at <https://aerobasegroup.com/nsn/6625-01-217-3668>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.059 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.766 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.766 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

10 single indicator single range

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Furnished Items And Quantity:

Screws 4; lock washers 4; hex nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.5 to 2.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.840 inches

Meter Body Diameter Behind Mounting Flange:

2.062 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 10.0 amperes, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Red accent mark at 6.6 amps

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0