

View Online at <https://aerobasegroup.com/nsn/6625-01-221-2729>

Circuit Current For Which Designed:

Ac

Overall Length:

5.2187 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.3125 inches

Overall Width:

4.3125 inches

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.500 inches

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6l seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+25.000 to 1000.000 hertz

Sensitivity Rating:

150.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.375 inches

Meter Body Diameter Behind Mounting Flange:

3.9687 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 5250.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 110.0 ac and 130.0 ac

Phase:

Single

Special Features:

Ruggedized

Special Markings:

On back, made in u. S. A.

Material:

Steel

Surface Treatment:

Paint

Special Test Features:

Complies with ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0