NSN 6625-01-222-0053

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-222-0053

| Circuit Current For Which Designed: |
|---|
| Dc |
| Overall Length: |
| 3.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.375 inches |
| Overall Height: |
| 4.422 inches |
| Overall Width: |
| 4.422 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Mounting Stud Length: |
| 0.625 inches |
| Furnished Items And Quantity: |
| Mtg hdw 4; term. Hdw 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0 to 1.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.813 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.960 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| |

4 threaded stud

Mounting Facility Type And Quantity:

NSN 6625-01-222-0053

Ammeter - Page 2 of 2



| Scale Graduation Type: |
|---|
| Linear single indicator single range |
| Measurement Range: |
| -50.0 to 50.0 amperes, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.250 inches |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ruggedized |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A310a0 |