NSN 6625-01-222-1020

Phase Sequence Indicator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-222-1020 Width: 4.438 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** Between 3.346 inches and 3.376 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** Between 3.346 inches and 3.376 inches Length: 6.625 inches **Current Type:** Ac Ac Voltage Rating: 120.0 volts and 240.0 volts and 480.0 volts Frequency Rating: 60.0 hertz **Mounting Stud Length:** Between 0.500 inches and 0.750 inches **Contact Quantity:** 3 **Contact Type:** Threaded stud **Presentation Type:** Meter **Mounting Arrangement Style:** Four hole/stud rectangular/square **Electrical Connection Quantity:** 3 **Mounting Facility Type And Quantity:** 4 threaded stud **Mounting Stud Diameter:** 0.250 inches **Features Provided:** Mounting hardware **Case Material:** Plastic Phase: Three **Special Features:**

Three neon lamps indicate when all three phases are energized; case material: or metal

Height:

4.438 inches

Special Test Features:

Conforms to the specifications of mil-i-16103d

NSN 6625-01-222-1020

Phase Sequence Indicator - Page 2 of 2



Supplementary Features	Supp	lementary	Features
------------------------	------	-----------	-----------------

Dial scale marked incorrect w/red band and correct w/green band

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A534h0