

View Online at <https://aerobasegroup.com/nsn/6625-01-223-3106>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

Between 2.655 inches and 2.745 inches

Overall Height:

0.488 inches

Overall Width:

1.810 inches

Mounting Hole Diameter:

0.120 inches

Scale Division Quantity:

20 single indicator single range

Distance Between Mounting Facility Centers:

1.250 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 2.360 inches and 2.420 inches

Meter Body Width Behind Mounting Flange:

Between 1.600 inches and 1.630 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-50.0 to 50.0 microamperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

0.488 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fii:

A310a0