

View Online at <https://aerobasegroup.com/nsn/6625-01-223-9843>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.355 inches

Overall Height:

1.640 inches

Overall Width:

1.980 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator 2nd range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.820 inches

Meter Body Diameter Behind Mounting Flange:

1.360 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

1 flange and 1 plug-in

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-6.0 to 6.0 amperes single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base and taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized; vertical mtg

Special Markings:

Word amps parallel to 1st scale; word volts parallel to 2nd scale, symbols + and - at opposite ends of scales

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Fan shape flush mtg

Supplementary Features:

Surf. Mtg in panel; ext mult

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0