## NSN 6625-01-224-0378

**Overall Length:** 

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-224-0378

| 2.470 inches  |
|---|
| Mounting Hole Diameter:   |
| Between 0.120 inches and 0.130 inches   |
| Overall Diameter:   |
| 2.695 inches  |
| Environmental Protection:   |
| Shock resistant and vibration resistant   |
| Mounting Bolt Circle Diameter:  |
| 2.440 inches  |
| Indicator Type:   |
| Dial w/pointer  |
| Installation Design:  |
| Panel   |
| Mounting Arrangement Style:   |
| Three hole/stud bolt circle   |
| Dial Scale Marking Color:   |
| Black single indicator single range   |
| Meter Depth Behind Mounting Flange:   |
| 1.430 inches  |
| Meter Body Diameter Behind Mounting Flange:   |
| 2.150 inches  |
| Movement Type:  |
| Moving coil, permanent magnet   |
| Background Color:   |
| White single indicator single range   |
| Pointer Color:  |
| Black single indicator single range   |
| Power Source:   |
| External  |
| Mounting Facility Type And Quantity:  |
| 3 unthreaded hole   |
|   |
| Features Provided:  |
| <b>Features Provided:</b> Zero adjuster   |
|   |
| Zero adjuster   |
| Zero adjuster  Movement Suspension Method:  |
| Zero adjuster  Movement Suspension Method:  Jewel pivot base  |
| Zero adjuster  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:                                     |
| Zero adjuster  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:  2 threaded stud                    |
| Zero adjuster  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:  2 threaded stud  Special Features: |

Nonhardened

## NSN 6625-01-224-0378

Electrical Frequency Meter - Page 2 of 2



| Desig |  |
|-------|--|
|       |  |

Round flush mtg

**Fsc Application Data:** 

Test set electronic equip.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0