

View Online at <https://aerobasegroup.com/nsn/6625-01-225-0563>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.410 inches

Overall Height:

3.320 inches

Overall Width:

3.890 inches

Mounting Hole Diameter:

0.140 inches

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

Between 2.240 inches and 2.260 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Frequency Response Range:

+25.000 to 400.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.200 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 150.0 amperes, ac single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Test Features:

Meets requirements of specification ansi c-39.1

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0